

Steifix 60

NATURAL SOAP - SPECIALLY PREPARED FOR STONE AND MINERAL SUBSTRATES

FOR PROFESSIONAL USE ONLY - REVISION DATE: 26th OCTOBER 2018

Steifix 60 is a natural soap specially prepared for stone. A combined wash, care and sealing fluid based on natural products, pH-value 8, for stone floors and mineral substrates.

Steifix 60 can be used on all type of stone floors, which can stand up for water. It gives the surface a powerful care film and confers a great cleaning ability.

Properties

Steifix 60 is a neutral natural product adjusted for stone floors, it gives the surface a powerful care film, and has a great cleaning ability, pH-value ready to use dissolution 8.0.

Steifix 60 is certified by Nordic Ecolabel and is environmental friendly.

Steifix 60 has a triple action:

- Cleaning action: **Steifix 60** is an efficient cleanser for stone or concrete floors. It penetrates into the pores.
- Protective action: since the first application, **Steifix 60** creating a film that confers brightness and facility to clean.
- Industrial cleaning: **Steifix 60** stops the penetration of oil, dust and grease, keeping the floor easy to wash.

Uses

First treatment:

- Make sure that the surface is perfectly clean, free from oily residues, dirt, dust. On concrete floors it is recommended to use **Evercrete® Pavishield** as a primer.
- Dilute with water in a ratio of 1:10.
- Apply with the aid of a mop, wax spreader, spatula, rubber spatula or washer-dryer.

Daily cleaning:

- Dilute in water in a ratio of 1:50.
- Spread out the product.
- Leave it on for some minutes. The solutions penetrates gradually.
- The application has to be repeated until the floor is saturated and the protection layer has been formed.
- To remove possible soap haloes scrubbing brush or similar.

Technical features

Packaging	5 liters tank
Shelf life	No deadline if stored sealed
Flammability	Not applicable
Environmental risk	None. The product is sophate free and biodegradable.
Storage	Store in a dry place and frost free.
Toxicity	None

Coverage rate

The coverage rate per square metres depends on the absorption capacity of the surface. In general, the first application the ratio dilution is 1:10 (1 part of steifix 60 on 10 parts of water). For the daily cleaning the ratio dilution is 1:50 (1 part of steifix 60 on 50 parts of water) depending the degree of soiling.

Limitazioni

Ecobeton products can be applied when surface temperature is above 5°C and air temperature between 10°C and 40°C. Avoid the frost during the curing phase. Do not apply if precipitations are foreseen in the following 24 hours.

Note:

The information contained in this sheet is accurate to the best of our current knowledge. The products are of the highest quality and standard with regard to production tolerances. As it is impossible to carry out any controls on the application of the product, no express or implicit guarantee is provided as regards the final result and no responsibility is accepted directly or indirectly by the use of the products. Users are encouraged to carry out tests before application.

For more details visit website:

www.ecobeton.com

e-mail for technical support:

europe@ecobeton.it

Ecobeton Italy s.r.l. unipersonal is a company certified with ISO 14001 environmental management system.

ecobeton

Ecobeton Europe
via G.Galilei, 47
36030 Costabissara (VI) Italy

T (+39) 0444 971893
E europe@ecobeton.it
I www.ecobeton.com