Cerbero Base

ACRYLIC WATER-BASED SEALER

FOR PROFESSIONAL USE ONLY - REVISION DATE: 05 SEPTEMBER 2025

Cerbero Base is a colorless water-based sealer developed for Ecobeton decorative products. It gives impermeability, chemical and stain resistances to microcementitious coatings. Cerbero Base is the first finish and it's used in combination with Cerbero Sealer to get a complete and safe protection.

Properties

- Single-component acrylic water-based sealer
- Microfiber roller, brush or airless pump application
- UV stable, not-yellowing
- Adhesion promoter for Cerbero Sealer
- Increased resistance to water and chemical compounds
- Fast drying

Uses

Cerbero Base is a colorless sealer suitable for cementitious overlays such as Ercole®, Microbond® and Microbond Finitura. It can be used as final sealer on walls and on not walkable surfaces, or it can be used as a primer in combination with Cerbero Sealer to increase the abrasion and wear resistances.

Technical data

Coverage rate (1)	120 - 150 g/m²
Packaging	1 kg - 5 kg
Appearance / Odour	White liquid / Typical
Number of applications	2 following instructions
Overcoating (2) (without sanding)	2 - 3 h (max 12 h)
Total drying time	12 - 24 h
Shelf Life	12 months if sealed in original container (3)

(1) It may vary depending on the surface porousity
(2) at 20°c and 65% of R.H.
(3) at temperature between 10°C and 30°C

Application

Cerbero Base should be apply on perfectly hardened, structurally sound, dry, free from dirt, grease, previous sealers that could inhibit the ahesion. Completely vacuum off any sanding dust.

Stir well before using.

Apply Cerbero Base using a microfiber roller (8 mm) or a brush. We recommend spraying the product onto the surface and then spreading it with a roller or brush in a "wet-on-wet" process. The product can also be applied with special airless equipment.

In case of highly porous surfaces or if environmental conditions require it, apply a first coat of Cerbero Base dilute by 50% of water. After drying proceed with the application of the second coat of product without dilution.

In case of low absorbent substrate best result is achieved applying two coats of Cerbero Base without dilution.

In the case of wall application, proceed from bottom to top.

If adhesive tape has been applied to delimit the laying area, remove the tape before the product has dried.

After about 2 hour, as soon as the surface is dry to the touch, proceed with the application on the protective finish Cerbero Sealer or GiGi Sealer following proper methods described on the related technical data sheets.

Warning

During application and curing of the product the surface and air temperature must not be lower than 10°C or higher than 30°C.

Do not apply on damp substrates or in the presence of rising damp.

Avoid puddles of the product during application.

Do not apply with radiant heating on.

Do not apply in windy or rainy weather or when rainfall is expected within 24 hours.

Do not expose material to frost.

When masking the surface treated with Cerbero Base, use only tape with acrylic adhesives that is suitable for delicate surfaces.

Note:
The information contained in the sheet is accurate to the best of our current knowledge. The products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly from their us. Buyers and users are encouraged to carry out their own test prior to application.

For more details visit website:
www.ecobeton.com
e-mail for technical support:
europe@ecobeton.it

ecobeton

Ecobeton Europe
via G. Galilei, 47
36030 Costabissara (VI) Italy

T (+39) 0444 971893
E europe@ecobeton.it
I www.ecobeton.com